



## BALL-FENCE GATE



### Features:

- Self-closing operation.
- Compatible with Ball-Fence hand rail system.
- Supplied with 42.4mm diameter galvanised hoop.
- Can swing inward or outward.
- Can be used in pairs for wider openings.

**Description:** Self-closing pedestrian gate.

**Compatibility:** Ball-Fence hand rail system.

**Material:** Mild steel.

**Finish:** Hot dip galvanised or powder coated Yellow.

**Operation:** Push open assisted closure.

**Gate swing:** 90 degrees.

**Gate stop:** Built-in.

**Opening:** Single gate 1.5 metres.

**Max. open:** Double gates 3 metres.

**Min. open:** No minimum.

**Adjustment:** Cut down on site.

**Height:** Top rail 1017mm above floor

**Clearance:** Overhead clearance not applicable.

**Mounting:** Existing posts, walls, optional posts available.

**Weight:** 18kgs gate assembly with 1.5 metre hoop.

| PART No.  | DESCRIPTION  |
|-----------|--|
| BFG       | Ball-Fence gate with hoop – Galvanised                 |
| BFG-P     | Ball-Fence gate with hoop – Galvanised & powder coated |
| KIT23     | Gate to post fixing kit – Up to 63mm diameter posts    |
| KIT24     | Gate to post fixing kit – Up to 90mm diameter posts    |
| C90SM     | 90mm surface mount bollard for mounting Ball-Fence     |
| BFGPWB-SM | Ball-Fence gate post – 48 x 1017mm                     |
| BFGH      | Additional 1.5 metre gate hoop                         |



## U-BARS Double Rail

### Features:

- Three sizes available in below ground or surface mount models.
- Heavy 3mm wall, 48.3mm diameter pipe.
- Fully welded one-piece construction.
- All models are galvanised and powder coated or galvanised only.
- Supplied ready for installation with no assembly required.

**Material:** Steel pipe 48.3mm diameter, 3mm wall.

**Finish:** Galvanised and powder coated or galvanised only.

**Height:** Above ground 1040mm.  
Below ground 300mm.

**Width:** 1000, 1500 or 2000mm.

**Weight:** UBD100 models 16kgs (approx.)  
UBD150 models 19.5kgs (approx.)  
UBD200 models 23.5kgs (approx.)

**Installation:** Surface mount models base plate 150 x 75 x 10mm.  
Below ground models come with welded concrete starter bars.

**Fixings:** Supplied with surface mount models.

| PART No.   | DESCRIPTION  |
|------------|--|
| UBD100SM   | U-Bar double rail 1 metre surface mount – Gal. & powder coat   |
| UBD100SM-G | U-Bar double rail 1 metre surface mount – Galvanised           |
| UBD100BG   | U-Bar double rail 1 metre below ground – Gal. & powder coat    |
| UBD100BG-G | U-Bar double rail 1 metre below ground – Galvanised            |
| UBD150SM   | U-Bar double rail 1.5 metre surface mount – Gal. & powder coat |
| UBD150SM-G | U-Bar double rail 1.5 metre surface mount – Galvanised         |
| UBD150BG   | U-Bar double rail 1.5 metre below ground – Gal. & powder coat  |
| UBD150BG-G | U-Bar double rail 1.5 metre below ground – Galvanised          |
| UBD200SM   | U-Bar double rail 2 metre surface mount – Gal. & powder coat   |
| UBD200SM-G | U-Bar double rail 2 metre surface mount – Galvanised           |
| UBD200BG   | U-Bar double rail 2 metre below ground – Gal. & pPowder coat   |
| UBD200BG-G | U-Bar double rail 2 metre below ground – Galvanised            |