



ER-RAIL GATE

Features:

- Self-closing operation.
- Post, wall or in-line mounting.
- Supplied with 1.2 metre aluminium rail.
- Economical single gate can swing inward or outward.
- Adjustable spring tension.
- Aluminium rails include hi-vis reflective tape.

PART No.	DESCRIPTION
ERG1200-PA	ER-Rail gate assembly
KIT23	Gate to post fixing kit – Up to 63mm diameter posts
KIT24	Gate to post fixing kit – Up to 90mm diameter posts
ER-RAK	ER-Rail gate in-line adaptor kit
C63SME	Surface mount bollard – 63.5 x 1.6 x 1000mm
C63BGE	Below ground bollard – 63.5 x 1.6 x 1000mm
C90SME	Surface mount bollard – 90 x 3.2 x 1000mm
C90BGE	Below ground bollard – 90 x 3.2 x 1000mm

Description: Self-closing pedestrian gate.

Compatibility: Designed for the ER-Rail system.

Material: Mild steel and aluminium.

Finish: Galvanised or powder coated Yellow.

Rail type: Single aluminium extrusion 80 x 30mm.

Operation: Push open/adjustable spring assisted closure.

Gate swing: 90 degrees.

Gate stop: Built-in.

Opening: Single gate operation.

Max. open: 1.2 metres.

Min. open: No minimum.

Adjustment: Length of rail can be cut down on site.

Height: Top rail 1000mm above floor.

Clearance: Overhead clearance not applicable.

Mounting: Post, wall or in-line.

Weight: 3.5kgs gate assembly with 1.2 metre rail.

