



MANUAL SWING GATES

Features:

- Manually operated swing gates.
- Can be mounted to bollards or any solid surface.
- Standard 5 metre rail can be cut down to any length.
- Aluminium rail includes hi-viz reflective panel.
- Gate receiver for wall or post mounting included.
- Full range of round and square bollards on request.

PART No.	DESCRIPTION
MSG5000	Manual 5 metre swing gate (bollard not included)
C90SM	Surface mount round bollard $-$ 90 x 5 x 1000mm
C90BG	Below ground round bollard $-$ 90 x 5 x 1380mm
C140SM	Surface mount round bollard $-$ 140 x 5 x 1200mm
C140BG	Below ground round bollard $-$ 140 x 5 x 1700mm
MSGRK	Additional gate receiver kit

Description:	Manual pedestrian or vehicle gate.
Material:	Galvanised steel assembly with powder coated aluminium rail.
Finish:	Powder coated Yellow with reflective.
Rail type:	Aluminium extrusion 145 x 40 x 5000mm.
Operation:	Push open / push close.
Gate swing:	Up to 180 degrees.
Gate stop:	Optional receiver post or wall receiver.
Max. open:	5 metres.
Min. open:	2 metres.
Adjustment:	Rail length can be cut down on site.
Height:	1000mm.
Mounting:	Can be post or wall mounted.
Weight:	35kgs gate assembly with 5 metre rail.



