



RETRACTABLE BOLLARDS

Features:

- Round 90mm diameter bollard locks in both extended and retracted positions.
- Mild steel hot dip galvanised with a powder coated finish or 316 marine grade stainless steel.
- Galvanised in-ground casing.
- Black anti-slip top surface and two reflective bands on powder coated model.
- Two unique, low cost 'T' handle keys supplied per order with additional keys available for purchase.
- Trouble free design with only two moving parts.
- Internal locking system can't be tampered with or fouled by dirt or water.

Material: Bollards 90mm diameter with 5mm mild steel or 3.05mm 316 stainless steel wall. In ground casing 140mm with 5mm wall mild steel.

Finish: Hot dip galvanised with powder coated finish or marine grade 316 stainless steel. In-ground casings for all models are hot dip galvanised.

Height: 900mm above ground.
1150mm below ground.

Weight: BR900 – 41.5kgs, Operating 12.5kgs.
BR900-SS – 38kgs, Operating 8.8kgs.

Locking: Unique internal locking mechanism with 'T' handle key.

Installation: Excavation and concrete footing.

PART No.	DESCRIPTION
BR900	Retractable bollard assembly – Galvanised and powder coated
BR900R	Replacement bollard – Galvanised and powder coated
BR900-SS	Retractable bollard assembly – 316 stainless steel
BR900R-SS	Replacement bollard – 316 stainless steel
BRKEY-P	Additional 'T' handle key for retractable bollard

